

SPRAYDET® 14EX

Aluminum Safe Multi-Metal Powder Spray-Wash Cleaner.
An inhibited alkaline powdered detergent for use in power spray wash cabinet systems, specially formulated to maintain foam control in problem situations.

SPRAYDET® 14EX

- ▶ Safe for use on ferrous and sensitive metal parts, rubber or plastic parts and electrical insulation.
- ▶ Removes mill oils, heavy greases, lubricants, carbonaceous soils and other soils commonly encountered in maintenance and production cleaning applications.
- ▶ Performs well at lower temperatures (140°) and short cycle times in many applications, providing particularly cost effective cleaning.
- ▶ Destroys foam build-up at operating temperatures (above 140°) with non-silicone defoamers.
- ▶ Provides operator safety. Will not erupt when mixed in hot water like caustic-based products. Incidental skin contact is normally harmless.
- ▶ Low odor product that has been thoroughly dedusted for operator comfort, safety and convenience.
- ▶ Biodegradable.

Use Instructions

In pressure spray wash cabinets and continuous spray systems, add ½ - 9 oz/gallon of hot water. Put SPRAYDET® 14EX on cabinet floor, close door and operate the sprayers for a few minutes to dissolve the cleaner.

Dissolves readily and may be added to an opened tank of hot water with minimal agitation.

Clean parts at 140° - 200° operating temperature. Rinse parts thoroughly after cleaning to prevent any residue.

Technical Data

Form	Free Flowing Powder
pH (use dilution)	11.5 to 12.5
Color	White
Rinseability	Excellent

**For Use Precautions and First Aid Information, please see the Material Safety Data Sheet.
Medical Emergency Hotline 1-800-246-2890**



C&H Chemical

222 Starkey Street, St. Paul, MN 55107-1885
1-800-966-2909
1-651-227-4343
Fax 1-651-227-2485