

SPRAYDET® CW

Alkaline Spray-wash Detergent

Spraydet® CW is a concentrated biodegradable, non-hazardous alkaline liquid detergent for use in power spray wash cabinet and conveyor systems, and agitated dip tanks in industrial maintenance and manufacturing operations..

SPRAYDET® CW

Spraydet® CW ...

- Quickly removes baked on carbon deposits, mill oils, heavy greases, lubricants, and other soils commonly encountered in manufacturing and maintenance applications.
- Is safe for use on aluminum and ferrous metal parts, including stainless steel, rubber or plastic parts.
- Is specially formulated to maintain effectiveness when used with hard water
- Will not build excess foam in spray cabinets at operating temperatures (above 140°F).
- Contains no silicone to interfere with new coatings or paint.
- Saves time and labor costs with effective cleaning productivity.

Use Instructions

*In pressure spray wash cabinets and conveyor spray systems, add 4 to 8 oz. or 3-5% detergent **Spraydet® CW** per gallon of hot water per system capacity..*

Spraydet® CW mixes readily. Add slowly to the surface of warm water with agitation to avoid spattering

Rinse parts with fresh water before drying. Most spray wash systems have a fresh rinse cycle.

To maintain correct product levels through extended periods between system water changes, use the C&H Titration Test Kit.

Clean at 140F to 200F, typically for 5 to 30 minutes.

Technical Data

Form.....Liquid.
Color Amber.
pH (use dilution) 10 to 11.5.
Storage Stability.....Excellent, keep from freezing.

**For Use Precautions and First Aid Information, please see the Material Safety Data Sheet.
Medical Emergency Hotline 1-800-246-2890**



C&H Chemical

222 Starkey Street, St. Paul, MN 55107-1885
1-800-966-2909
1-651-227-4343
Fax 1-651-227-2485