

SPRAYDET® EX-LIQUID

Aluminum Safe Multi-Metal Liquid Spray-Wash Cleaner.

An inhibited alkaline liquid detergent for use in power spray wash cabinet systems, specially formulated to maintain foam control in problem situations.

SPRAYDET® EX-LIQUID

- ▶ Safe for use on ferrous and sensitive metal parts, rubber or plastic parts.
- ▶ Removes mill oils, heavy greases, lubricants, carbonaceous soils and other soils commonly encountered in maintenance and production cleaning applications.
- ▶ Performs well at lower temperatures (140°) and short cycle times in many applications, providing particularly cost effective cleaning.
- ▶ Destroys foam build-up at operating temperatures (above 140°) with non-silicone defoamers.
- ▶ Provides operator safety. Will not erupt when mixed in hot water like caustic-based products. Incidental skin contact is normally harmless.
- ▶ Low odor product for operator safety and convenience.
- ▶ Biodegradable – contains no VOC's.

Use Instructions

In pressure spray wash cabinets and continuous spray systems, add ½ - 9 oz/gallon of hot water. Add SPRAYDET® EX-Liquid directly to machine. Operate equipment according to manufacturer's instructions.

Clean parts at 140° - 200° operating temperature. To maintain correct product concentrations use a C&H Titration Test Kit.

Technical Data

Form	Liquid
pH (use dilution)	11.5 to 12.5
Color	Slight Amber
Rinseability	Excellent

**For Use Precautions and First Aid Information, please see the Material Safety Data Sheet.
Medical Emergency Hotline 1-800-246-2890**



C&H Chemical

222 Starkey Street, St. Paul, MN 55107-1885
1-800-966-2909
1-651-227-4343
Fax 1-651-227-2485