

SPRAYDET® S

Alkaline Spray-wash Detergent

Spray•Det S is a concentrated alkaline liquid detergent for use in power spray wash cabinet and conveyor systems, and agitated dip tanks in industrial maintenance and manufacturing operations..

SPRAYDET® S

Quickly removes baked on carbon deposits, mill oils, heavy greases, lubricants, and other soils commonly encountered in manufacturing and maintenance applications.

➤ Is safe for use on ferrous metal parts, including stainless steel, and rubber or plastic parts.

➤ Is specially formulated to maintain effectiveness when used with hard water

➤ Will not build excess foam in spray cabinets at operating temperatures (above 140°F).

➤ Contains no silicone to interfere with new coatings or paint.

➤ Saves time and labor costs with effective cleaning productivity.

Use Instructions

In pressure spray wash cabinets and conveyor spray systems, add 4 to 8 oz. Spray•Det S per gallon of hot water.

Spray•Det S mixes readily. Add slowly to the surface of warm water with agitation to avoid spattering

Clean at 140F to 200F, typically for 5 to 30 minutes.

Rinse parts with fresh water before drying. Most spray wash systems have a fresh rinse cycle.

To maintain correct product levels through extended periods between system water changes, use the C&H Titration Test Kit.

Technical Data

Form.....Liquid.
Color Amber.
pH (use dilution) 13 to 13.5.
Storage Stability.....Excellent, keep from freezing.

**For Use Precautions and First Aid Information, please see the Material Safety Data Sheet.
Medical Emergency Hotline 1-800-246-2890**



C&H Chemical

222 Starkey Street, St. Paul, MN 55107-1885

1-800-966-2909

1-651-227-4343

Fax 1-651-227-2485